



product description: the pipes are intended for installation to the distribution of low voltage  
 the pipes are suitable for mechanical protection of conductors and cables inside halls (indoor)  
 the pipes are made of galvanized steel bar at the top (zinc layer 3 - 4  $\mu\text{m}$ ) and isolation layer inside

material: steel

temperature resistance: -45 - +90 °C

mechanical resistance: 750 N / 5 cm

classification according to EN 61386-1 ed. 2: 33522

certification: EN 61386-1 ed.2:09, EN 61386-22:04

storage: EN 60721-3-1



accessories: clamps: 3613 A\_S, 3616 A\_S, 3623 A\_S, 3629 A\_S, 3636 A\_S, 3648 A\_S

item number	dn outer $\varnothing$ (mm)	di min. inner $\varnothing$ (mm)	length = package (m)	package weight (kg)
<b>3313_B</b>	18,9	13,5	10	1,9
<b>3313_XX</b>	18,9	13,5	100	18,7
<b>3316_B</b>	21,4	16	10	2,3
<b>3316_XX</b>	21,4	16	100	23,5
<b>3323_B</b>	28,9	23	10	3,3
<b>3323_XX</b>	28,9	23	50	16,4
<b>3329_B</b>	35,2	29	10	4,5
<b>3329_XX</b>	35,2	29	50	22,3
<b>3336_B</b>	43	36	5	3,0
<b>3336_XX</b>	43	36	25	14,8
<b>3348_B</b>	54,9	48	5	3,7
<b>3348_XX</b>	54,9	48	25	18,3