



product description: it is used to divide the interior of the trunking, thus allowing a better manipulation with the inserted cables and clarity
 installation is done by „click” onto „T”-rail on trunking’s bottom
 possibility to install in places with risk of flammable gases and vapor – danger zone 2
 possibility to install in places with explosive risk of dust – danger zone 22

item number: PEP 60_HD
 material: PVC - Pb-free
 self-snuffing: yes, within 30 s
 temperature resistance: -5 - +60 °C
 color: white
 length: 2 m
 length tolerance: ±10 mm
 package: 2 m / 32 m
 weight: 0,23 kg/m
 meets the requirements: EN 50085-1 ed.2:06, EN 50085-2-1:07
 storage: ČSN 64 0090



chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate
 NO: aceton, benzen, chlorinated hydrocarbons, tetrachlorocarbon

compatible with:

- EKE 100X60
- EKE 140X60
- EKE 180X60
- PK 110X70 D
- PK 140X70 D
- PK 170X70 D
- PK 210X70 D
- PK 110X65 D
- PK 130X65 D