


item number	for width of cable tray (A) mm	height H mm	B	thickness of metal sheet mm	weight	٨
NIXVKR 62_IX	62	14,8	409	0,6	0,31	٨
NIXVKR 125_IX	125	14,8	472	0,6	0,58	٨
NIXVKR 250_IX	250	14,8	597	0,6	1,22	٨
NIXVKR 500_IX	500	14,8	858	0,6	2,95	٨



product description: This cover is used to cove the cross-over NIXKR.

To fix the cover use cover fixutres NIXUV and NIXSM 6X10

material: IX - stainless steel AISI 304

(AISI 316, AISI 316L only to order)

á 1 pc sales amount:

meets the requirements: ČSN EN 61537:02


classification : ČSN 73 0895 P 90-R

> DIN 4102-12 E 90 STN 92 0205 PS 90

Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with

maintained functionality in fire

ČSN EN 60721-3-1 storage:







Risk of injury from cutting

Although the cable trays are produced with maximum effort to minimize sharper edges, it is necessary to wear protective gloves to carry, grip and work with cable elements.

Electricity injury

As individual components of cable management systems are made of electrical conductive material, it is essential not to work with a system near live electrical parts. Infringement of the safety regulations may cause serious injury of health or death.

Safe Use

Under normal and foreseeable conditions of use, there are no risks to consumers, provided that proper installation and usage are carried out in accordance with the installation manual.

recycling codes:



3-30/07/2025