

type number:

GZS_XX

product description: designated for visual correction of welds and defective places on galvanized construction

almost visual non-recognizable from fresh galvanized surface

quickdrying

zinc dust 99 % netto share

contains pigments of zinc, aluminium and resin for treated steel protection

electrically conductive

bright silver colour

temperature resistance till +300 °C

chemicals resistance

contents 400 ml



use:

Use this container only in well aired hall with room temperature. Before every spraying shake the container intensely for 2 minutes till the mixing marble inside moves freely. Try the tolerance of sprayed material. The treated surface get rid of rust and grease. Apply the spray from 25-30 cm distance. If needed more coating wait for well drying the previous one.

Before use shake the container well.

sales amount:

á 1 pc

contents:

Acetone, hydrocarbons, C9, aromas

producer:

Pematex

WARNING

Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust / fume / gas / mist / vapours / spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves / protective clothing / eye protection / face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER / doctor / ... / if you feel unwell. Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F. Dispose of contents / container to hazardous or special waste. In use may form flammable / explosive vapour-air mixture. Repeated exposure may cause skin dryness or cracking.

