




product description:

designed for distribution system with voltage 400 V and with maximum current 16 A
for installation in environments with increased humidity and dust
inlets for cables or pipes of 16, 20 and 25 mm in accordance with EN 60423
possibility to install on materials of fire classes A1 to D

material - box: PE

material - cover: PP

color: light gray RAL 7035 / white RAL 9003

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 850 °C

fire class for underlying material: A1-D

protection types: IP 54

weight: 99 g

meets the requirements: ČSN EN 60670-1, ČSN EN IEC 60670-1 ed. 2:21

storage: ČSN 64 0090

8135_HA - boxes packed loosely in carton, 30 pcs of boxes; color - white RAL 9003

8135_KA - boxes packed loosely in carton, 30 pcs of boxes; color - light grey RAL 7035

accessories:

terminal plate S-96; SP-96

multipolar terminal plate TYP210, TYP310, TYP412, TYP512, TYP612

screwless terminal plates TYP015, TYP016, TYP017, TYP018

recycling symbols:



WARNING

risks associated
with

using the products: incorrect electrical installation can cause a fire - we recommend the connection to be carried out exclusively by an authorized person

follow the manufacturer's installation instructions according to the installation instructions and videos

damage to the product - if the box is visibly damaged, stop using it

under normal and foreseeable conditions of use, the installed box does not pose any risks to consumers