




product description: for insertion pipes into the BV xx bushing
the manufacturer recommends using a flexible pipes LPE (23xx/LPE-x)

item number	ØA (mm)	ØB (mm)	weight (g)	for pipe sizes	package in bag (pcs)	package in carton (pcs)
BK 16_AA	19	27	4	EN 16	40	600
BK 16_CSN_AA	24	40	7	ČSN 16	40	320
BK 20_AA	23	27	5	EN 20	40	560
BK 23_AA	30	40	7	ČSN 23	40	280
BK 25_AA	28	40	7	EN 25	40	320
BK 32_AA	35	40	7	EN 32	40	320

material: PE (halogen-free)
color: orange
self-snuffing: no
temperature resistance: -5 - +60 °C (short-time +90 °C)
flaming loop test: 650 °C
fire class for underlying material: A1
meets the requirements: EN 60 670-1
storage: ČSN 64 0090



recycling symbols:



ending



foil



cardboard



WARNING

risks associated
with

using the products: incorrect electrical installation can cause a fire - we recommend the connection to be carried out exclusively by an authorized person

when installing the ending into the steel reinforcement, be extra careful, use appropriate protective equipment

follow the manufacturer's installation instructions according to the installation instructions and videos

damage to the product - if the ending is visibly damaged, stop using it

under normal and foreseeable conditions of use, the installed ending does not pose any risks to consumers