



product
description:

used for main connection according to ČSN 1-35 2000-4-41

equipotential

use only for bonding the zero potential, cannot be used as a phase connection etc.

can be used in the box KO 125 E - the box is specially adapted for mounting

possibility to install into boxes KT 250/1 and KT 250/L

dimension: 126 x 60 x 50 (126 x 60 x 62 when the screws removed at maximum)

for 4 conductors with cross-section 2,5-6 mm²

for 6 conductors with cross-section 4-16 mm²

for 2 conductors with cross-section 10-95 mm²

for 1 grounding strap 30x4 mm

material: PA6

color: brown GOBI

self-snuffing: yes, within 30 s

flaming loop test: 850 °C

meets the requirements: EN 60998-1; EN 60998-2

weight: 279 g

storage: ČSN 64 0090

EPS 2_XX - 1 pc of equipotential terminal plate in carton, equipotential terminal plate without cover

EPS 2_X1 - 1 pc of equipotential terminal plate in carton, equipotential terminal plate with cover

recycling symbols:



terminal plate



screws, clamp strap



cardboard



WARNING

risks associated
with

using the products: incorrect electrical installation can cause a fire - we recommend the connection to be carried out exclusively by an authorized person

follow the manufacturer's installation instructions according to the installation instructions and videos

damage to the product - if the box is visibly damaged, stop using it

make sure the product is properly attached and secured to prevent accidental loosening

under normal and foreseeable conditions of use, the installed product does not pose any risks to consumers