



product description:

designed for distribution system with voltage 400 V and with maximum current 16 A
 box can be used with terminal S-96 or SP-96 or two terminals S-66, which are separated by a partition
 possibility to connect two different circuits of up to 400 V separated by a partition
 tips for marking hole centres for installation holes in the double wall
 mounting screws are fitted with a triple thread for quick installation

material: PVC (Pb Free)

color: yellow

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 850 °C

fire class for underlying material: A1-F

weight: 160 g

meets the requirements: ČSN EN 60670-1, ČSN EN IEC 60670-1 ed. 2:21

storage: ČSN 64 0090

KO 110/L_NA - cover screws and screws for mounting into double wall inserted together with partition P 110 L into box, each box with cover V 110 L sealed in shrink foil and labelled; 28 pcs of boxes stacked in carton


KO 110/L_ST - screws for mounting into double wall installed in the box, cover screwed to the box and box labelled; 28 pcs of boxes stacked in carton

accessories:

terminal plate S-66; S-96; SP-96
 screwless terminal plates TYP015, TYP016, TYP017, TYP018

auxiliary tools:

saw-drill VPT 40
 universal carrier VPTU

recycling symbols:

⚠ WARNING

risks associated with

using the products: incorrect electrical installation can cause a fire - we recommend the connection to be carried out exclusively by an authorized person

follow the manufacturer's installation instructions according to the installation instructions and videos

damage to the product - if the box is visibly damaged, stop using it

under normal and foreseeable conditions of use, the installed box does not pose any risks to consumers